

Canon**XF705**

AUFLÖSUNG	FARBSAMPLING	FARBTIEFE	BILDFREQUENZ	CODEC	Mbps
3840 x 2160	YCC 4:2:2	10 Bit	59,94p, 29,97p, 23,98p, 50,00p, 25,00p	H.265/HEVC	160 Mbps/110 Mbps
1920 x 1080	YCC 4:2:2	10 Bit	59,94p, 29,97p, 23,98p, 50,00p, 25,00p	H.265/HEVC	60 Mbps/45 Mbps
			59.94i, 50.00i		60 Mbps/45 Mbps
			120p, 100p		180 Mbps
3840 x 2160	YCC 4:2:0	8 Bit	29,97p, 23,98p, 25,00p	H.264/XF-AVC	160 Mbps
1920 x 1080	YCC 4:2:0	8 Bit	59,94p, 29,97p, 23,98p 50,00p, 25,00p	H.264/XF-AVC	45 Mbps
			59.94i, 50.00i	H.264/XF-AVC	35 Mbps
			120p, 100p	H.264/XF-AVC	45 Mbps
1280 x 720	YCC 4:2:0	8 Bit	59,94P	H.264/XF-AVC	180 Mbps
1920 x 1080	YCC 4:2:0	8 Bit	59,94p, 29,97p, 23,98p 50,00p, 25,00p	H.264/MP4	8 Mbps
					35 Mbps/8 Mbps